TECHNICAL SPECIFICATIONS Smappee Genius



- Gateway between monitoring system and Smappee cloud.
- High-end HEMS/BEMS allowing dynamic load balancing and smart control.
- Compatible with various communication protocols.
- Future-proof thanks to over-the-air updates.
- Connectivity via Ethernet, Wi-Fi or 3G/4G (optional).

The Genius is the gateway between the monitoring system and the Smappee cloud, ensuring secure data storage from different components via Ethernet, Wi-Fi or 3G/4G (optional). In case of network outage, it will store the data for two days. It communicates and interacts with third party components, Smappee Gas & Water and Smappee Switch. Thanks to these various options, the Genius allows Smappee Infinity to take on the role of a Home or Building Energy Management System (HEMS or BEMS) and guarantee optimised self-consumption.

- Dimensions: 108 × 69 × 25 mm (4.25 x 2.72 x 0.98 inches) Product certifications: CE, FCC, RCM
- Weight: 119 g [4.20 oz]
- Working temperature: -10 °C to 60 °C (14 °F to 140 °F)
- Storage temperature: -20 °C to 90 °C (-4 °F to 194 °F)
- Relative humidity: 0 % 95 %, non-condensing
- Operating altitude: 0 2,000 m (0 6,562 feet)
- EMC: IEC 61326-1, FCC 47 part 15
- Safety: IEC 60950-1
- IP rating (IEC 60529): IP X0
- Spectrum: EN 300 328 V2.1.1 and EN 300 220

- Connectivity:
 - Ethernet 100BASE-T
 - Wi-Fi 2.4 GHz
 - 2G/3G/4G (optional USB Dongle)
 - RF 433 MHz/915 MHz
 - Smappee Bus B
- Accessories included:
 - Wall mounting plate
 - Smappee Bus cable 150 cm (59 inches)

